

BMA002 - , BMA003 - , BMA004 - , BMA008 - , BMA009-

/
/

58% ± 2% (ISO 3233:1998)

: 125 (: 216)
4.64 (m²/lt) - 125 ()

24

	5°C	10°C	25°C	35°C
(ISO 1517:73)	4.5	4	2	1.5
	24	24	12	12

	5°C	10°C	25°C	35°C
Intersmooth 460 SPC	12	ext 10	ext 6	ext 4
Interswift 655	12	ext 10	ext 6	ext 4
: Intersmooth 360, 365, 465		465HS SPC		Intersmooth 460 SPC

BMA002- , BMA003- , BMA009- 1
()

	390 g/lt 257g/kg	(EPA method 24) (1999/13/EC)
Interswift 655		2001 10 IMO (IMO AFS/CONF/26).

가

• Interswift 655 2001 “ ”

(AFS 2001) :

, DNV

(SSPC-SP1)

/
Interswift 655

655 가

Interswift 655

() Interswift
(Sa2.5(ISO 8501-1:1988))

Interswift 655
가

Interswift 655
가

:

(3,000 p.s.i., 211kg/ cm²)

가

Interswift 655

().

Intersmooth SPC,

Interswift 655

:

:

Sa2.5 (ISO 8501-1:1988)

SSPC-SP10

() International GTA007 (: 5%).

- : 0.46 - 0.66mm (18-26thou)
- : 176kg/cm² (2500 p.s.i.)

International GTA007

가 International GTA007 가

ANSI/ASC Z49.1 "

가

가

가

USA/Canada - Medial Advisory Number 1-800-854-6813
Europe - Contact 44 (0)191 4696111. For advice to Doctors & Hospitals only contact 44 (0)207 6359191
R.O.W. - Contact Regional Office (see page 4 of Data Sheet)

: 3
: 6

(3,000 p.s.i., 211kg/cm²)

BMA002- , BMA003- , BMA009-
가) .

→ / , → / →
→ / , → / →

Interswift 655 Intertuf 674 Intertuf 23 Interswift 655 Intertuf 203
가 가

()

3 (5)
21-27 (70-80)

가
()

가

'ext'=extended overcoating period

20	20			
20	: 38.5			
가				
25 (77)	12	25 (77)	6	
가		(,)		

가

가

가

가

가

가

가



International

Akzo Nobel

© Akzo Nobel 2006