Interstores_® OBM Range



A dedicated, easy to apply OBM range


Vessels applied since launch

Product Description

Interstores_® is a dedicated range of On Board Maintenance (OBM) products, specifically designed for easy application by ships crews at sea and in port. Engineered to meet OBM product performance expectations, our crew friendly products are specifically designed for brush and roller application.

Key Features

	Interstores Polyurethane Finish	Interstores Alkyd Finish	Interstores Epoxy Primer	Interstores Alkyd Primer
Description	Two pack glossy polyurethane cosmetic finish	One pack glossy alkyd cosmetic finish	Two pack epoxy primer	One pack alkyd primer
Areas	For use on topsides, boottops, external decks and superstructures	For use on topsides, boottops, external decks and superstructures	Ideal for use in high traffic areas and cargo holds	Suitable for all substrates above the waterline
Features	Good durability Long term recoatability	Easily recoatable with itself Notable flow out of brush marks	Proven performance over contaminated steel Fast drying to aid efficient repair	Fast Drying Compatible with a wide range of finishes



Roller (1 Pass)



Benchmark

Engineered for Ease of Application









To find out more visit: www.international-marine.com



Interstores_® OBM Range



A dedicated, easy to apply OBM range

Supply Locations

We deliver a dedicated product offer in the key shipping connection points based on major global trading patterns. Our new streamlined port and product offer for Interstores ensures that you receive the best range of products to meet your OBM requirements with a minimum lead time.



Global Key Ports

- Busan
- Ulsan
- Kobe
- Tokyo
- Antwerp
- Hamburg
- Rotterdam
- notteruan
- Felixstowe
- Suez
- Marseilles
- Piraeus
- Genoa
- Capetown
- Durban
- Algeciras
- Gibraltar
- Valencia

- Istanbul
- Dubai
- Fujairah
- Guangzhou
- Shanghai
- Kaoshiung
- racomang
- Tanjung Pelepas
- Singapore
- Colon: Cristobal
- Balboa
- Houston
- Los Angeles
- Miami
- New Orleans
- New York
- Seattle
- Rio de Janeiro

Property	Interstores Polyurethane	Interstores Alkyd	Interstores Epoxy Primer	Interstores Alkyd Primer
Colours	ISA210 - Topcoat White ISA220 - Topcoat Red ISA230 - Topcoat Green ISA240 - Topcoat Surf Grey ISA250 - Topcoat Grey ISA260 - Topcoat Black	ISA510 - Topcoat White ISA520 - Topcoat Red ISA530 - Topcoat Green ISA540 - Topcoat Surf Grey ISA550 - Topcoat Grey ISA560 - Topcoat Black	ISA420 - Primer Red Part A ISA430 - Primer Green Part A ISA450 - Primer Grey Part A	ISA710 - Primer White ISA720 - Primer Grey ISA730 - Primer Red
Finish	Gloss Finish	Gloss Finish	Matt Finish	Matt Finish
Volume Solids %	54% ±3% (ISO 3233:1998)	47% ±3% (ISO 3233:1998)	65% ±2% (ISO 3233:1998)	48% ±2% (ISO 3233:1998)
Theoretical coverage	13.5 m ² /litre at 40 microns dft	11.75 m ² /litre at 40 microns dft	8.67 m ² /litre at 75 microns dft	6.4 m ² /litre at 75 microns dft
Application	Brush, Roller	Brush, Roller	Brush, Roller	Airless Spray, Brush, Roller
Touch dry @ 25°C	1.5 hours	6 hours	2 hours	1.5 hours
Hard dry @ 25°C	10 hours	24 hours	4 hours	3.5 hours
Thinner	Not required. Use International GTA713, GTA733, GTA056 in exceptional circumstances	Not required. Use International GTA004 in exceptional circumstances	Not required. Use International GTA220 in exceptional circumstances	Not required. Use International GTA004 in exceptional cases
Shelf Life	18 months at 25°C. Subject to reinspection thereafter. Store in dry, shaded conditions away from sources of heat and ignition.	24 months at 25°C. Subject to reinspection thereafter. Store in dry, shaded conditions away from sources of heat and ignition.	Part A - 18 months at 25°C. Part B - 12 months at 25°C. Subject to reinspection thereafter. Store in dry, shaded conditions away from sources of heat and ignition.	12 months at 25°C. Subject to reinspection thereafter. Store in dry, shaded conditions away from sources of heat and ignition.

For each of our products the relevant Product Data Sheet, Material Safety Data Sheet and package labelling comprise an integral information system about the product in question. Copies of our Product Data Sheets and Material Safety Data Sheets are available on request or from our website.

Unless otherwise agreed in writing, all products supplied and technical advice or recommendations given are subject to the Conditions of Sale of our supplying company and the provisions of the relevant product data sheet

To find out more visit: www.international-marine.com

